

Specifications

Model		General Purpose	Worksite	Recreational	EC homologated version "Streetlegal special"
Engine	Make	KUBOTA D902-E2-UV			
	Type	3-cylinders, 4-cycle, diesel, OHV			
	Displacement	cc	898		
	Horsepower	kW (PS)/rpm	16.1 (21.9)@3200		
Fuel capacity	U.S.gals (ℓ)	7.4 (28)			
Transmission	Variable hydro transmission (VHT)				
Max. Traveling speed	km/h	40			
Wheels, drive system	4, 4WD w/2WD selection				
Differential lock	Standard; foot operated with mechanical holder				
Gear selection	Hi-Med-Lo range forward, neutral, reverse				
Brakes	Front / Rear	Wet-disc brake			
	Parking brake	Rear wheel, hand lever			
Steering	Hydrostatic power				
Suspension	Front / Rear	Independent, MacPherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorber			
Dimensions	Length	mm	2990	3030	
	Width	mm	1520		
	Height, overall	mm	2015	2125	
	Front tread centers	mm	1150		
	Rear tread centers	mm	1180		
	Wheelbase	mm	1965		
	Ground clearance	front axle mm	215	200	
		rear axle mm	195		
Turning diameter	m	7.9			
Max. rolling weight (Towing capacity)	kg	590			
Payload capacity	kg	740			
Weight	kg	850	875	925	
Cargo bed	Width	mm	1320		
	Length	mm	1180		
	Depth	mm	290		
	Volume	m ³	0.455		
	Bed height (unloaded)	mm	800	805	
	Cargo bed load	kg	500		
Sound level, operator ear	db. (A)	87			
Tires	Front	25×10–12 Knobby, 6PLY	25×10–12 HDWS, 6PLY	25×10–12 ATV, 6PLY	25×10–12 HDWS, 6PLY
	Rear	25×10–12 Knobby, 6PLY	25×10–12 HDWS, 6PLY	25×11–12 ATV, 6PLY	25×10–12 HDWS, 6PLY
Front guard	—		Std.	Std.	Std.
Body color	Orange		Orange	Camo	Orange
Hydraulic bed lift	—		Std.	Std.	Std.
Speedometer	—		—	Std.	Std.

* The company reserves the right to change the above specifications without notice.

* This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN. Phone (01844) 214500 Fax (01844) 216685

Web site: <http://www.kubota.co.uk/> E-mail: sales@kubota.co.uk